

mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft
25	1	37	1,46	10	150	100	4,00	90	1,300	0,873
40	1 1/2	52	2,05	10	150	140	5,50	90	2,000	1,343
50	2	61	2,40	10	150	150	6,00	90	2,100	1,410
65	2 5/8	88	3,46	10	150	175	6,00	90	2,200	1,477
80	3 1/8	93	3,66	10	150	250	10,00	90	2,700	1,810
100	4	119	4,69	10	150	350	14	90	4,000	2,686

NA	LA	NEU	EMEA	SA	AP	AU
----	----	-----	------	----	----	----



## 6J511 EN

**Fuel-oil S&D 10 bar (150 psi) - standard duty  
EN 13765 arrêté TMD**

**Inner wire:** Galvanised steel wire

**Tube:** Polypropylene film

**Cover:** Grey PVC coated fabric with longitudinal yellow stripe

**Outer wire:** Galvanised steel wire

**Use:** Fuel and oil suction and delivery.

Specially designed for tank truck applications

**Safety factor:** 4:1

**Temperature:** -30 °C +80 °C (-22 °F +176 °F)

**Electrical Conductivity:** Ensured by the 2 wires in contact with fittings

**Electrical Resistance:** ≤ 2.5 Ohm/mt up to DN 50mm (2");

≤ 1 Ohm/mt over DN 50mm (2")